






	0	1	2	3	4	5	6	7	8	9	
A											A
B	RAZDELILNIKA		RAZDELILNIK B8D.SB.PR.3								B
	SISTEM NAPAJANJA		TN-C-S								
	NAPETOST:		400/230V 50Hz								
	Pi (kW)=		24,2kW								
	fp=		1								
C	fi=		0,2								C
	Pk(kW)=		4,84								
	cos(fi)=		0,95								
	Ik(A)=		7,36								
D											D
E											E
F											F

 UI Rakovške cete 19 1381 Rakek www.ekprojekt.eu gsm: 051366748	"4" NACRT ELE.INST.IN OPREMA STIKALNI BLOK B8D.SB.PR.3-TIP O FAZA :PZI	Datoteka: S28_B8D.SB.PR.3		Nacrt: S28	Init.:	Rev.:	Stran: 1
		Datum: 18. 09. 2018	Function:	Location:	Skupaj strani: 5	Naslednja Stran: 2	









PO hisni razdelilnik KVM 4-v. 48/56TE – PO mont. nizek okvir

Neto sirina	359,00mm
Neto visina	714,00mm
Neto globina	95,00mm
Izvedba	Podomet za stene z vrati
Material vrata	Jeklana ploševina
Vrste	4
Stevilo modulov (TE) v vrsti	12+2
Stopnja zasšite	IP30

PO medij. razdelilnik MVM 4-v. 12/14TE – PO mont. niz. okvi

Neto sirina	359,00mm
Neto visina	714,00mm
Neto globina	95,00mm
Izvedba	Podomet za stene z vrati
Material vrata	Jeklana ploševina
Vrste	4
Stevilo modulov (TE) v vrsti	12+2
Stopnja zasšite	IP30